

UNICUS® 4i

4 AND 5-STAGE HIGH PRESSURE BREATHING AIR COMPRESSORS

This game-changing filling station employs our state-of-the-art control system centered around a 15-inch HMI touch screen interface, which allows the operator to manage the entire system from the single-point touch screen. UNICUS 4i has several innovative optional features including BAUER Gas-Tek™ monitoring system, Lab On Locale 2™ and RFID Reader.

EFFECTIVE: 01/01/21

- › **PRESSURE:**
5000 to 6000 PSIG
(345 to 414 BAR)
- › **CHARGING RATE:**
13 to 26.4 SCFM
(368 to 748 L/MIN)
- › **POWER:**
10 to 20 HP
(7.5 to 15 kW)



› UNICUS 4i



› UNICUS 4i
(SHOWING INSIDE FRONT)



› UNICUS 4i
(SHOWING INSIDE BACK)

STANDARD SCOPE OF SUPPLY

- › BAUER breathing air purification system with B-SECURUS
- › **BAUER 15-inch HMI touch-screen** interface
- › Solid state auto cascade system
- › Compressor low oil pressure and high temperature safety shutdowns
- › Emergency stop push button
- › Ergonomic and intuitive system-operations panel
- › Ergonomically designed stainless steel fill adaptors with integral bleed valve
- › Automatic condensate drain system with non-corrosive condensate reservoir and integrated float sensor and automatic “Full” indication and compressor shutdown
- › Two (2) ASME code stamped air cylinders installed in an integral rack designed to hold four cylinders
- › NFPA 1901 2016 edition compliant 3 position containment fill station accommodates SCBA or SCUBA cylinders up to 31” overall length

AVAILABLE ACCESSORIES
(FACTORY INSTALLED)

- › **BAUER Gas-Tek™** gas monitoring system
- › **Lab on Locale 2™** accredited remote air testing system
- › **RFID Reader** which reads and records data from the RFID equipped cylinders
- › Hose reel for 100’ of high pressure breathing air hose
- › Reg/RF
- › Dual Fill/3 position
- › Tri Fill/3 position
- › Additional air storage cylinders

SYSTEM FOOTPRINT

DIMENSIONS L x W x H inches (mm)
› 101” x 38” x 78” (2565mm x 965mm x 1981mm)
WEIGHT pounds (kg) › 4350 - 4550 lb (1973 - 2064 kg)
*Weights are based on a unit equipped with 4 ASMEs

TECHNICAL DATA

Model	Charging Rate ¹		Number of Stages	Motor		FAD ²	Purification System
	SCFM	L/MIN		HP	kW		
5000 PSIG (345 BAR)							
UNICUS 4i -20 - E3	21	595	4	15	11	17.5	P5 B-SECURUS
UNICUS 4i -26 - E3	26.4	748	4	20	15	22	P5 B-SECURUS
6000 PSIG (414 BAR)							
UNICUS 4i -13- E1	13	368	4	10	7.5	10.8	P2 B-SECURUS
UNICUS 4i -13- E3	13	368	4	10	7.5	10.8	P2 B-SECURUS
UNICUS 4i -18- E3	18	510	4	15	11	15	P5 B-SECURUS
UNICUS 4i -25- E3	25.2	714	5	20	15	21	P5 B-SECURUS

1) Based on recharging an 80 cubic foot tank from 500 to 3000 psig.
2) Compressor capacity referenced to standard inlet conditions. Tolerance +/- 5%

OPTIONAL ACCESSORIES - UNICUS 4i

Item	Description	
0001	Electronic carbon monoxide monitor complete with calibration kit wired for alarm and shutdown. (calibration gas included)	GT/CO/III
0002	Each additional ASME 5000 PSIG cylinder with relief valve and mounting clamps	/CYL-9/5K
0003	Each additional ASME 6000 PSIG cylinder with relief	/CYL-9/6K
0004	Panel mounted remote fill hose connection. Includes bulkhead fitting, adjustable regulator for up to 6000 PSIG service, gauge, isolation valve and quick connect/disconnect fitting (hose no included)	/RF/REG
0005	UN4i remote fill hose connection including adjustable regulator for up to 6000 PSIG service, gauge and isolation valve connected to a cabinet enclosed hose reel with 100 feet of hose rated for 6000 PSIG service	UN4i/RF/REL-9
0006	DUAL-FILL, high/low, quick connect fill system (specify fill pressures)	DUAL-FILL/3 position
0007	TRI-FILL, high/low/SCUBA, quick connect fill system (specify fill pressures)	TRI-FILL/3 position
0008	LAB-ON-LOCALE 2 includes 12 accredited tests, unlimited non-accredited tests and control module swap out in first year.	LOL4
0009	RFID SCBA Data Logging	RFID4i
0010	RFID DATA TAGS Each Kit includes 25-each tags	KIT-0557
0011	Fire Edition Paint Scheme	
0012	B-VIRUS FREE™	



Compressors, Inc. Bauer, Oceanus, BP II, Dive Mate, Maxi Verticus, Mini Verticus, Securus, Capitano II, Junior II, Mariner II, Unicus III, Mini Unicus, TCom Lite, TCom, Vertecon, Triplex, and Classic II are all trademarks owned by Bauer Compressors, Inc. of Northfolk, Virginia.

www.ss.fm (International Sales) eks@ss.fm
 www.bauerair.com (US Sales) mail@bauerair.com
 Tel : (936) 564-3483